

# New Trend Computer

www.tokoNTC.com

Yogyakarta : 0274-7821780, 378143, 6689343

Lumajang: 0334-7711222, 893516

Probolinggo : 0335-429450

Contact: Fred Endratno

Tel : +62-334-7711222

Fax: +62-888-895



Email: info@tokontc.com

YM : trend\_comp200@yahoo.com


Homepage: \_\_\_\_\_

<http://www.tokoNTC.com>

## THIN CLIENT / PC STATION PRICE LIST

ATTN:		Company Name:		Date:			
ITEM NAME	PICTURE	SPECIFICATION	EXW PRICE		DIMENSION		
			QTY(unit)	USD	Inner Box (cm)	Carton Box (cm)	
NC230-M		Max User Per PC	10 users when use a Server Host OS	Min 5u	\$97,00	27.50L*17W*7H Inner Box Packing: * Terminal x 1 * Power Adapter x 1 * Quick Install Guide x 1 * CD Disk x 1	55L*35W*33H Carton Box Packing: 20 x Inner Boxes
			30 users when use a desktop OS	5 - 10u	\$87,00		
		Support OS	Windows XP Professional/Media Center Edition 2005 Windows Server 2003, Small Business Server 2003 <b>Windows 2008, Windows Vista</b>	>10	\$77,00		
		Video Resolution	640x480, 800x600, 1024x768, 1280x1024, 1440x900 <b>(16 Bit or 24 Bit color)</b>				
		Connect Port	* PS/2 Keyboard x 1      * PS/2 Mouse x 1 * Speaker Out x 1      * VGA Port x 1 * Power Switch x 1      * DC In Port x 1 * RJ-45 Ethernet Port x 1      * <b>USB Port x 1</b> * <b>Microphone Port x 1</b> * <b>TV Port</b>				
		Connect Range	Around 100 meters				
		Terminal Size	Width: 11.5 cm/4.5 inches Height: 2.6 cm/1 inch Depth: 11.5 cm/4.5 inches				
		Terminal Weight	Terminal weight: 0.36kg Shipping weight: 0.8kg/1.7lbs				
		Limitation	* Do not support 3D games * Do not support full screen home theater applications * Max users per Host PC will support depends upon the host system capabilities.				
		Warranty	1 year				
NC130		Max User Per PC	10 users when use a Server Host OS	Min 5u	\$70,00	27.50L*17W*7H Inner Box Packing: * Terminal x 1 * Power Adapter x 1 * Quick Install Guide x 1 * CD Disk x 1	55L*35W*33H Carton Box Packing: 20 x Inner Boxes
			30 users when use a desktop OS	5 - 10u	\$65,00		
		Support OS	Windows XP Professional/Media Center Edition 2005 Windows Server 2003, Small Business Server 2003	>10	\$60,00		
		Video Resolution	640x480, 800x600, 1024x768, 1280x1024 (16 Bit color)				
		Connect Port	* PS/2 Keyboard x 1      * PS/2 Mouse x 1 * Speaker Out x 1      * VGA Port x 1 * Power Switch x 1      * DC In Port x 1 * RJ-45 Ethernet Port x 1				
		Connect Range	Around 100 meters				
		Terminal Size	Width: 11.5 cm/4.5 inches Height: 2.6 cm/1 inch Depth: 11.5 cm/4.5 inches				
		Terminal Weight	Terminal weight: 0.36kg Shipping weight: 0.8kg/1.7lbs				
		Limitation	* Do not support 3D games * Do not support full screen home theater applications * Max users per Host PC will support depends upon the host system capabilities.				
		Warranty	1 year				
NC400 17" All in one PC		Max User Per PC	10 users when use a Server Host OS	Min 5u	\$205,00	46L*14W*48H Inner Box Packing: * All-In-One PCstation x 1 * Power Adapter x 1 * Quick Install Guide x 1 * CD Disk x 1	56L*46W*43H Carton Box Packing: 4 x Inner Boxes
			30 users when use a desktop OS	5 - 10u	\$195,00		
		Support OS	Windows XP Professional/Media Center Edition 2005 Windows Server 2003, Small Business Server 2003	>10	\$185,00		
		Video Resolution	640x480, 800x600, 1024x768, 1280x1024 (16 Bit color)				
		Connect Port	* PS/2 Keyboard x 1      * PS/2 Mouse x 1 * Speaker Out x 1      * VGA Port x 1 * Power Switch x 1      * DC In Port x 1 * RJ-45 Ethernet Port x 1      * No USB Port				
		Connect Range	Around 100 meters				
		Brightness:	500cd/m2				
		Contrast Ratio:	500/1				
		Pixel Pitch:	0.294mm				
		Response Time:	8ms				
Ideal Resolution	1024x 768						
AC input:	AC100-240V, 50/60Hz, 12V, 3.5A						
Power Consumpt	37W, DPMS (2W)						
Warranty	1 year						

NC200	 	Max User Per PC	10 users when use a Server Host OS 30 users when use a desktop OS	Min 5u	\$95,00	27.50L*17W*7H Inner Box Packing: * Terminal x 1 * Power Adapter x 1 * Quick Install Guide x 1 * CD Disk x 1	55L*35W*33H Carton Box Packing: 20 x Inner Boxes
		Support OS	Windows XP Professional/Media Center Edition 2005 Windows Server 2003,Small Business Server 2003	5 - 10u	\$90,00		
		Video Resolution	640x480,800x600,1024x768,1280x1024(16 Bit color)	>10	\$85,00		
		Connect Port	* PS/2 Keyboard x 1 * PS/2 Mouse x 1 * Speaker Out x 1 * VGA Port x 1 * Power Switch x 1 * DC In Port x 1 * RJ-45 Ethernet Port x 1 * <b>USB Port x 1</b>				
		Connect Range	Around 100 meters				
		Terminal Size	Width: 24.5 cm/9.64 inches Height: 4.5 cm/1.77 inch Depth: 14 cm/5.51 inches				
		Terminal Weight	Terminal weight: 0.24kg Shipping weight: 0.8kg/1.7lbs				
		Limitation	* Do not support 3D games * Do not support full screen home theater applications * Max users per Host PC will support depends upon the host system capabilities.				
		Warranty	1 year				
		NC230	 	Max User Per PC	10 users when use a Server Host OS 30 users when use a desktop OS		
Support OS	Windows XP Professional/Media Center Edition 2005 Windows Server 2003,Small Business Server 2003			5 - 10u	\$85,00		
Video Resolution	640x480,800x600,1024x768,1280x1024(16 Bit color)			>10	\$80,00		
Connect Port	* PS/2 Keyboard x 1 * PS/2 Mouse x 1 * Speaker Out x 1 * VGA Port x 1 * Power Switch x 1 * DC In Port x 1 * RJ-45 Ethernet Port x 1 * <b>USB Port x 1</b>						
Connect Range	Around 100 meters						
Terminal Size	Width: 11.5 cm/4.5 inches Height: 2.6 cm/1 inch Depth: 11.5 cm/4.5 inches						
Terminal Weight	Terminal weight: 0.36kg Shipping weight: 0.8kg/1.7lbs						
Limitation	* Do not support 3D games * Do not support full screen home theater applications * Max users per Host PC will support depends upon the host system capabilities.						
Warranty	1 year						
NC300				Max User Per PC	10 users when use a Server Host OS 30 users when use a desktop OS	Min 5u	\$80,00
		Support OS	Windows XP Professional/Media Center Edition 2005 Windows Server 2003,Small Business Server 2003	5 - 10u	\$75,00		
		Video Resolution	640x480,800x600,1024x768,1280x1024(16 Bit color)	>10	\$70,00		
		Connect Port	* PS/2 Keyboard x 1 * PS/2 Mouse x 1 * Speaker Out x 1 * VGA Port x 1 * RJ-45 Ethernet Port x 1				
		Connect Range	<b>Around 10 meters</b>				
		Terminal Size	Width: 11 cm/4.33 inches Height: 2.8 cm/1.10 inch Depth: 6.5 cm/2.55 inches				
		Terminal Weight	Terminal weight: 0.5kg (3units) Shipping weight: 0.8kg/1.7lbs				
		Limitation	* Do not support 3D games * Do not support full screen home theater applications * Max users per Host PC will support depends upon the host system capabilities.				
		Warranty	1 year				
		NC100	 	Max User Per PC	10 users when use a Server Host OS 30 users when use a desktop OS	Min 5u	\$70,00
Support OS	Windows XP Professional/Media Center Edition 2005 Windows Server 2003,Small Business Server 2003			5 - 10u	\$65,00		
Video Resolution	640x480,800x600,1024x768,1280x1024(16 Bit color)			>10	\$60,00		
Connect Port	* PS/2 Keyboard x 1 * PS/2 Mouse x 1 * Speaker Out x 1 * VGA Port x 1 * Power Switch x 1 * DC In Port x 1 * RJ-45 Ethernet Port x 1						
Connect Range	Around 100 meters						
Terminal Size	Width: 17 cm/6.69 inches Height: 3.5 cm/1.37 inch Depth: 13 cm/5.11 inches						
Terminal Weight	Terminal weight: 1.54g/0.34lbs Shipping weight: 0.8kg/1.7lbs						
Limitation	* Do not support 3D games * Do not support full screen home theater applications * Max users per Host PC will support depends upon the host system capabilities.						
Warranty	1 year						

<b>NC400 15"</b> <b>All in one</b> <b>PC</b>		Max User Per PC 10 users when use a Server Host OS 30 users when use a desktop OS Support OS Windows XP Professional/Media Center Edition 2005 Windows Server 2003, Small Business Server 2003 Video Resolution 640x480, 800x600, 1024x768, 1280x1024 (16 Bit color) Connect Port * PS/2 Keyboard x 1 * PS/2 Mouse x 1 * Speaker Out x 1 * VGA Port x 1 * Power Switch x 1 * DC In Port x 1 * RJ-45 Ethernet Port x 1 * No USB Port Connect Range Around 100 meters Brightness: 500cd/m2 Contrast Ratio: 500/1 Pixel Pitch: 0.294mm Response Time: 8ms Ideal Resolution 1024x 768 AC input: AC100-240V, 50/60Hz, 12V, 3.5A Power Consumption 37W, DPMS (2W) Warranty 1 year	<b>Min 5u</b> \$185,00 <b>5 - 10u</b> \$175,00 <b>&gt;10</b> \$170,00	43L*15W*40H Inner Box Packing: * All-In-One PCstation x 1 * Power Adapter x 1 * Quick Install Guide x 1 * CD Disk x 1	57L*44W*46H Carton Box Packing: 4 x Inner Boxes
		Max User Per PC 10 users when use a Server Host OS 30 users when use a desktop OS Support OS Windows XP Professional/Media Center Edition 2005 Windows Server 2003, Small Business Server 2003 Video Resolution 640x480, 800x600, 1024x768, 1280x1024 (16 Bit color) Connect Port * PS/2 Keyboard x 1 * PS/2 Mouse x 1 * Speaker Out x 1 * VGA Port x 1 * Power Switch x 1 * DC In Port x 1 * RJ-45 Ethernet Port x 1 * No USB Port Connect Range Around 100 meters Brightness: 1000cd/m2 Contrast Ratio: 1000/1 Pixel Pitch: 0.294mm Response Time: 8ms Ideal Resolution 1440x900 AC input: AC100-240V, 50/60Hz, 12V, 3.5A Power Consumption 37W, DPMS (2W) Warranty 1 year	<b>&lt;100u</b> Not Support <b>min 100u</b> \$230,00 <b>500u</b> \$220,00		
		Max User Per PC 10 users when use a Server Host OS 30 users when use a desktop OS Support OS Windows XP Professional/Media Center Edition 2005 Windows Server 2003, Small Business Server 2003 Video Resolution 640x480, 800x600, 1024x768, 1280x1024 (16 Bit color) Connect Port * PS/2 Keyboard x 1 * PS/2 Mouse x 1 * Speaker Out x 1 * VGA Port x 1 * Power Switch x 1 * DC In Port x 1 * RJ-45 Ethernet Port x 1 * No USB Port Connect Range Around 100 meters Brightness: 1000cd/m2 Contrast Ratio: 1000/1 Pixel Pitch: 0.51mm Response Time: 8ms Ideal Resolution 1680x1050 AC input: AC100-240V, 50/60Hz, 12V, 3.5A Power Consumption 37W, DPMS (2W) Warranty 1 year	<b>&lt;100u</b> Not Support <b>min 100u</b> \$250,00 <b>500u</b> \$240,00		
		Max User Per PC 10 users when use a Server Host OS 30 users when use a desktop OS Support OS Windows XP Professional/Media Center Edition 2005 Windows Server 2003, Small Business Server 2003 Video Resolution 640x480, 800x600, 1024x768, 1280x1024 (16 Bit color) Connect Port * PS/2 Keyboard x 1 * PS/2 Mouse x 1 * Speaker Out x 1 * VGA Port x 1 * Power Switch x 1 * DC In Port x 1 * RJ-45 Ethernet Port x 1 * No USB Port Connect Range Around 100 meters Brightness: 1000cd/m2 Contrast Ratio: 1000/1 Pixel Pitch: 0.51mm Response Time: 8ms Ideal Resolution 1680x1050 AC input: AC100-240V, 50/60Hz, 12V, 3.5A Power Consumption 37W, DPMS (2W) Warranty 1 year	<b>&lt;100u</b> Not Support <b>min 100u</b> \$250,00 <b>500u</b> \$240,00		